



Highprofile Classic

Paulownia Shutter Cheat Sheet

V290824

Characteristics of Paulownia Timber

Pale coloured timber	Fine grain texture
Extremely light weight	Native to Asia
High strength to weight ratio	Extremely fast growing

Composition

100% paulownia frames, stiles and blades

Construction

2 stage rebated, fluted mortise and tenon joint

Blades

Elliptical 64mm, 89mm, 114mm

Frames*

Flat L 47mm, 57mm, 67mm
 Insert L 47mm, 67mm, 74mm
 Beaded L 47mm, 67mm, 74mm
 Z Standard, Z Large Lip, Z Bevelled
 Z Deco, Z Crown, Face Fit Deco
 Modern, Face Fit Deco Traditional

Stiles

Flat 41mm, 51mm, 65mm, 90mm
 Flat Rabbet 41mm, 51mm
 Beaded 51mm

Installations

Hinged, Multi-fold, Fixed,
 Sliding, Tier on tier, Bay, Corner

Control Rods

Hidden Tilt, Clearview, Traditional
 Centre, Offset 40, Euro 180

Colours & Finish

13 standard whites, custom colours,
 2-pac polyurethane paint

Shapes

Available

Extras

Security bolt, Fly screen, Blade open/
 close tool, Blade closure pull ring,
 Cupboard-catch



Product Warranty

Structural	25 Years
Paint	5 Years
Custom	5 Years
Components	3 Years

Please Note: This Cheat Sheet is an overview of available options. Please always refer to the Product Guide for more detailed information.

Warranty Limits Installation Type	Width			Height			Panel Breaks			
	Min	Max	Max Non-Warranty	Min	Max	Max Non-Warranty	Mid-Rail(s) Required	Approximate Split Rotation by Blade Size		
								64	89	114
Hinged: All Types	250	1050	1200	400	3000	N/A	1800, 2700	1100	1300	1200
Double Hinged	250	600	700	400	3000	N/A	1800, 2700	1100	1300	1200
Panel Only	250	1050	1200	400	3000	N/A	1800, 2700	1100	1300	1200
Fixed	250	1050	1200	400	3000	N/A	1800, 2700	1100	1300	1200
Sliding	250	1050	1200	400	3000	N/A	1800, 2700	1100	1300	1200
Multi-Fold	250	600	700	400	3000	N/A	1800, 2700	1100	1300	1200

Panels under 400 mm high will be supplied hinges loose.